

**DATA CARRIER WITH POWER INPUT CONTROL****Publication number:** JP2002521770T**Publication date:** 2002-07-16**Inventor:****Applicant:****Classification:**

- International: G06F1/26; G06K19/07; H04B1/59; G06F1/26;  
G06K19/07; H04B1/59; (IPC1-7): G06K19/07;  
G06F1/26; H04B1/59

- European: G06K19/07T

**Application number:** JP20000562862T 19990727

**Priority number(s):** EP19980114198 19980729; WO1999EP05392  
19990727

**Also published as:**

WO0007141 (A1)  
US6581842 (B2)  
US2001035461 (A1)  
MXPA01001033 (A)  
CN1311886 (A)


more &gt;&gt;

Report a data error here

Abstract not available for JP2002521770T

Abstract of corresponding document: **WO0007141**

A data carrier, especially a chip card, comprising at least one send/receive antenna (SP) in addition to a downstream rectifier circuit (GR) providing a supply voltage (VDD, VSS) for at least one circuit unit (S1, Si). A voltage control circuit (RS) is connected in parallel to the supply voltage terminals of the circuit unit (s) (S1, Si). A signal that is proportionate to the control signal of the voltage control circuit (RS) can be picked up at the output of the voltage control circuit (RS). Said output is connected to the control input of a controllable clock signal generator (TSG) that provides the clock signal (C1) for the at least one circuit unit (S1, Si).



Data supplied from the esp@cenet database - Worldwide